	Туре	L #	Hits	Search Text	DBs	Time Stamp
Н	BRS	L1	911	(monitor\$5 or detect\$5 or inspect\$5 or measur\$5 or calculat\$5 or detect\$5	USPAT; US-PGPUB; EPO;	2003/04/16
F	טאט	<u>-</u>	7 ⊥	<pre>determin\$5) near7 (dust near4 surface)</pre>	JPO; DERWENT; IBM_TDB	08:46
V	BRS	Τ,8	597	1 and @ad<=19970418	USPAT; US-PGPUB; EPO;	2003/04/16
١	ţ	t	(+ \$114\$ (\$\$ \ +\\\ -\\ ++\\	JPO; DERWENT; IBM_TDB	08:49
J	משמ	л	022004	(light or laser or optic\$3) near3	USPAT; US-PGPUB; EPO;	2003/04/16
Ü	נוענ	E F	7000	(beam or source or light)	JPO; DERWENT; IBM_TDB	08:53
>	משמ	T)	သ သ သ	מ אאל זע	USPAT; US-PGPUB; EPO;	2003/04/16
4	byo		707	o alla io	JPO; DERWENT; IBM_TDB	10:04
п	משמ	T) O	_	oo and annii ango	USPAT; US-PGPUB; EPO;	2003/04/16
Ú	U.S.	1100	ų	רי שוות מההדדמוורפ	JPO; DERWENT; IBM_TDB	10:04

	4	З	2	<u> </u>	
Л	.,_				
					Comments
					Error
	0				Error Definition
)	0	0	0	0	Err

PAT-NO:

JP409061293A

DOCUMENT-IDENTIFIER: JP 09061293 A

TITLE:

DUST DETECTOR ON OPTICAL APPARATUS

PUBN-DATE:

March 7, 1997

INVENTOR-INFORMATION:

NAME

INOUE, TOSHIYUKI

ASSIGNEE-INFORMATION:

NAME

COUNTRY

FUJI PHOTO FILM CO LTD

N/A

APPL-NO:

JP07217172

APPL-DATE:

August 25, 1995

INT-CL (IPC): G01M011/00, G01N021/15, G01N021/88

ABSTRACT:

PROBLEM TO BE SOLVED: To detect dust deposited to a surface of an optical part such as a cover glass, a lens and a mirror in an optical apparatus of a scanning optical system or the like.

SOLUTION: Scattered light 2b caused by laser scanning light 2a transmitting through a cover glass 6 which is scattered by dust 10 deposited to a surface of the cover glass 6 is led to a sensor 14 by an optical rod 12 to be converted into an electric signal, and the electric signal is compared with a reference value by a detecting means 16 to determine whether dust exists or to evaluate a dust quantity, thereby detecting the dust 10 deposited to the surface of the cover glass 6.

COPYRIGHT: (C)1997,JPO